



APPLICATIONS

Eni Arnica 100 is a high performance antiwear hydraulic oil, specifically designed to meet the needs of modern, high pressure, industrial and mobile equipment hydraulic systems.

It's formulated with selected base oils treated with "low zinc" technology ensuring excellent thermal, oxidative and hydrolytic stability.

Eni Arnica 100 is recommended for outdoor equipment which are likely to operate in wide temperature range, such as systems where cold start-up and high operating temperatures are typical (marine applications). It's suitable also for indoor manufacturing equipment that incorporates control systems requiring minimal viscosity change with temperature.

CUSTOMER ADVANTAGES

- Suitable for applications operating in a wide temperature range thanks to a high viscosity index and an excellent viscosity stability
- Suitable for hydraulic systems with very thin filters (3 microns)
- Prolongs oil change life extending re-lubrication intervals thanks to very high thermo-oxidative stability
- Protects hydraulic pumps and components thanks to outstanding antiwear property
- Helps prevent aeration and cavitation damage in low residence time systems thanks to rapid air release
- Compatible with a wide variety of component metallurgy
- Maximizes water removal system efficiency thanks to excellent demulsibility

SPECIFICATIONS & APPROVALS

- AISE 127
- Commercial Hydraulics
- AFNOR NF E 48603 HV
- Eaton Vickers M-2950-S level
- Eaton Vickers I-286-S level
- CETOP RP 91 H HV
- REXROTH RD 90220-01/12.10
- Linde
- DIN 51524-3 HVLP
- ISO 11158 L-HV
- BS 4231 HSE





CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m ³	889
Viscosity at 40°C	ASTM D 445	mm ² /s	100
Viscosity index	ASTM D 2270	-	143
Pour point	ASTM D 97	°C	-36
Demulsibility at 54°C	ASTM D 1401	mins	20



eni